



PROFESSIONAL



PROFESSIONAL
PERAČI POD PRITISKOM

- NERĐAJUĆI ČELIK -

Generalni distributer za Srbiju: ECO Steam

ECO Steam · Vojvode Putnika 43, Trnava, 35000 Jagodina · tel. +381 63 640 101 · info@eco-steam.rs · www.eco-steam.rs





AR PROFESSIONAL expands its portfolio with a new range of stainless steel pressure washers, designed to deliver high performance, reliability and versatility across professional cleaning applications. Stainless steel ensures corrosion resistance, structural strength and long service life, even in demanding environments.

Each model results from advanced research and development, offering consistent performance and meeting the needs of sectors such as industry, marine, automotive and food.

Careful material selection and attention to details ensure safe, efficient and durable machines for professionals seeking quality and reliability. Backed by Annovi Reverberi's expertise, AR PROFESSIONAL stands for innovation, efficiency and long-lasting performance in professional cleaning.

AR PROFESSIONAL proširuje ponudu novom linijom peraća pod pritiskom od nerđajućeg čelika, visokih performansi, pouzdanosti i svestranosti u profesionalnom čišćenju. Nerđajući čelik obezbeđuje otpornost na koroziju, čvrstinu i dug vek trajanja i u najtežim uslovima.

Svaki model je rezultat naprednog istraživanja i razvoja, uz postojane performanse prilagođene sektorima kao što su industrija, brodogradnja, auto-industrija i prehrambena industrija.

Kvalitet materijala i pažljiva izrada garantuju bezbedne, efikasne i dugotrajne mašine. Zahvaljujući iskustvu Annovi Reverberi, AR PROFESSIONAL je sinonim za inovaciju, efikasnost i trajne performanse.

ECO Steam je generalni distributer AR Professional serije u Srbiji.



AR5X-10.15CM	str. 04
AR5X-15.18CT	str. 04
AR5X-15.23CT	str. 04
AR5X-21.23CT	str. 04
AR5X-15.23CTF	str. 04
AR5X-21.20CTF	str. 04



AR9X-15.55CH	str. 06
AR9X-15.55CL	str. 06
AR9X-18.44CH	str. 06
AR9X-21.38CH	str. 06
AR9X-30.28CH	str. 06
AR9X-42.22CH	str. 06



AR5X-10.15HM	str. 08
AR5X-15.18HT	str. 08



AR6X-15.18HT	str. 10
AR6X-15.23HT	str. 10
AR6X-21.23HT	str. 10
AR6X-15.23HTF	str. 10
AR6X-15.23HTP	str. 10



AR5XE-13.16HT	str. 12
AR5XE-8.18HT	str. 12



AR5X - 10.15 CM
 AR5X - 15.18 CT
 AR5X - 15.23 CT
 AR5X - 21.23 CT
 AR5X - 15.23 CTF
 AR5X - 21.20 CTF


MAX bar
150÷230


MAX l/h
600÷1260


kW
3.0÷9.6



Flanged pressure unloader /
 Prirubnički regulacioni ventil



Elastic coupling /
 Elastična spojnica
 AR5X-15.23CTF | AR5X-21.20CTF



Optional hose reel /
 Opciona metalica creva

GENERAL FEATURES / OPŠTE KARAKTERISTIKE

- Professional high pressure washer
- Stainless steel sturdy frame with solid rubber wheels for a better maneuverability
- Stainless steel cover
- Stainless steel pressure gauge (Ø63 mm)
- Pressure regulation valve
- Viton** hot water gaskets
- Profesionalni perač pod visokim pritiskom
- Robusni ram i točkovi sa punom gumom za bolju upravljivost
- Poklopac od nerđajućeg čelika
- Manometar od nerđajućeg čelika (Ø63 mm)
- Regulacija pritiska
- Zaptivke za toplu vodu od **Viton**

TECHNICAL DATA / TEHNIČKI PODACI

MODEL	AR ŠIFRA	 MAX		 MAX										
		bar maks.	bar radni	psi maks.	psi radni	l/h radni	gph radni	KS	kW	kW radni	o/min	V	Hz	Kg
AR5X-10.15CM	15885	150	120	2175	1740	600	158	3	2.2	3	1450	230 ~	50	54
AR5X-15.18CT	15886	180	150	2610	2175	900	238	5.5	4	5	1450	400 3 ~	50	61
AR5X-15.23CT	15887	230	200	3335	2900	900	238	7.5	5.5	7.4	1450	400 3 ~	50	70
AR5X-21.23CT	15888	230	200	3335	2900	1260	333	9.6	7	9.6	1450	400 3 ~	50	70
AR5X-15.23CTF	15889	230	200	3335	2900	900	238	7.5	5.5	7.4	1450	400 3 ~	50	67.5*
AR5X-21.20CTF	15890	200	180	2900	2610	1260	333	8.5	6.2	8	1450	400 3 ~	50	72.2


*On request / Na zahtev

(AR5X-10.15CM)
HRC+VRZ / HJK + VRZ



- Triplex pump with ceramic pistons and connecting rod system with nichel plated pump head
- Flanged valve
- Bronze connecting-rods
- Automatic by-pass valve with pump head pressure discharge
- Induction motor with thermal protection
- Time delayed auto stop/start with stop for motor overloading (TST)

- Pumpa sa 3 keramička klipa, klipnjačno-kolenasti pogon, glava pumpe od niklovanog mesinga
- Prirubnički ventil
- Bronzane klipnjače
- Automatski bypass ventil sa rasterećenjem pritiska u glavi pumpe
- Indukcioni elektromotor sa termičkom zaštitom
- Potpuno zaustavljanje sa odlaganjem perača (TST)



STANDARD ACCESSORIES / SERIJSKA OPREMA



code / šifra

inlet / ulaz

M22x1,5 M 14 mm

M22x1,5 M

1/4 NPT M

outlet / izlaz

M22x1,5 F

1/4 NPT F

-

compatible with / kompatibilno sa



10 m

code / šifra

inlet / ulaz

M22x1,5 F

outlet / izlaz

M22x1,5 F

LOGISTIC DATA / LOGISTIČKI PODACI

MODEL	DIM. PAKOVANJA	DIM. UREĐAJA	KG GROSS	EU	PUN KAMION	20"	40"	40"HQ
	(DxŠxV) mm	(DxŠxV) mm	kg					
AR5X-10.15CM	685x550x550	-	57	6	198	66	144	-
AR5X-15.18CT	685x550x550	-	65	6	198	66	144	-
AR5X-15.23CT	685x550x550	-	74	6	198	66	144	-
AR5X-21.23CT	685x550x550	-	73	6	198	66	144	-
AR5X-15.23CTF	685x550x550	-	70,5*	6	198	66	144	-
AR5X-21.20CTF	685x550x550	-	75,4	6	198	66	144	-

*On request / Na zahtev



AR9X - 15.55 CH
 AR9X - 15.55 CL
 AR9X - 18.44 CH
 AR9X - 21.38 CH
 AR9X - 30.28 CH
 AR9X - 42.22 CH



MAX bar
220÷550



MAX l/h
900÷2520



KS
22-24.5



Optional automatic hose reel with non marking hose 20 m/
 Opciona automatska motolica sa crevom bez tragova 20 m



gear box / reduktor obrtaja
 šif. 29593



throttle control / automatski regulator gasa
 šif. 51534

AR9X-15.55CH

GENERAL FEATURES / OPŠTE KARAKTERISTIKE

- Professional gasoline powered high pressure washer with HONDA motor and LONCIN (AR9X-15.55CL)
- Stainless steel cover
- Sturdy frame and solid rubber tyres for a better maneuverability
- Pressure regulation valve
- Stainless steel pressure gauge (Ø63 mm)
- Fuel tank with mechanical level indicator
- Throttle control
- Thermostatic valve
- Stainless steel safety valve
- Ceramic nozzle
- Automatic hose reel (20 m) on request
- Profesionalni perač pod visokim pritiskom sa benzinskim motorom HONDA i LONCIN (AR9X-15.55CL)
- Poklopac od nerđajućeg čelika
- Robusni ram i točkovi sa punom gumom za bolju upravljivost
- Regulacija pritiska
- Manometar od nerđajućeg čelika (Ø63 mm)
- Rezervoar sa mehaničkim indikatorom nivoa goriva
- Reduktor broja obrtaja
- Termostatski ventil
- Sigurnosni ventil od nerđajućeg čelika
- Keramička dizna
- Na zahtev automatska motolica creva (20 m)

TECHNICAL DATA / TEHNIČKI PODACI

MODEL	AR ŠIFRA	 MAX				 MAX		o/min	motor	kW	 KG NET
		bar maks.	bar radni	psi maks.	psi radni	l/h radni	gph radni				
AR9X-15.55CH	15981	550	500	7977	7251	900	237	1550	HONDA GX690 - 22	16.5	151.5
AR9X-15.55CL	15982	550	500	7977	7251	900	237	1550	LONCIN LC2V80FD - 24.5	20	157.5
AR9X-18.44CH	16057	440	400	6381	5801	1080	285	1550	HONDA GX690 - 22	16.5	151.5
AR9X-21.38CH	16058	380	350	5510	5076	1260	333	1550	HONDA GX690 - 22	16.5	151.5
AR9X-30.28CH	16059	280	250	4061	3625	1800	475	1550	HONDA GX690 - 22	16.5	150.5
AR9X-42.22CH	16060	220	180	3190	2610	2520	665	1550	HONDA GX690 - 22	16.5	150.5



XW / SHP



gear box (GB) /
reduktor obrtaja (CR)

- Triplex pump with ceramic pistons and connecting rod system with brass pump head
- Automatic by-pass valve with pump head pressure discharge

- Pumpa sa 3 keramička klipa, klipnjačno-kolenasti pogon, glava pumpe od mesinga
- Automatski bypass ventil sa rasterećenjem pritiska u glavi pumpe



STANDARD ACCESSORIES / SERIJSKA OPREMA



code / šifra

inlet / ulaz	M24x1,5 M	M24x1,5 M	1/4 NPT M
outlet / izlaz	M24x1,5 F	1/4 NPT F	-



10 m



code / šifra

inlet / ulaz	M24x1,5 F	-
outlet / izlaz	M24x1,5 F	-

LOGISTIC DATA / LOGISTIČKI PODACI

MODEL	DIM. PAKOVANJA	DIM. UREĐAJA	KG GROSS	EU	PUN KAMION	20"	40"	40"HQ
	(DxŠxV) mm	(DxŠxV) mm	kg	kom				
AR9X-15.55CH	740x1140x1600	980x706x900	171,5	1	72	30	64	-
AR9X-15.55CL	740x1140x1600	980x706x900	177,5	1	72	30	64	-
AR9X-18.44CH	740x1140x1600	980x706x900	171,5	1	72	30	64	-
AR9X-21.38CH	740x1140x1600	980x706x900	171,5	1	72	30	64	-
AR9X-30.28CH	740x1140x1600	980x706x900	170,5	1	72	30	64	-
AR9X-42.22CH	740x1140x1600	980x706x900	170,5	1	72	30	64	-



AR5X - 10.15 HM
AR5X - 15.18 HT



MAX bar
150÷180



MAX l/h
630÷900



kW
3.0÷5.0

AR5X-15.18HT



Flanged pressure unloader /
Prirubnički regulacioni ventil



Optional hose reel /
Opciona motalica creva

GENERAL FEATURES / OPŠTE KARAKTERISTIKE

- Professional hot water high pressure washer
- Stainless steel cover
- Sturdy frame and solid rubber tyres for a better maneuverability
- Pressure regulation valve
- Thermal-magnetic circuit breaker
- 20 l fuel tank with mechanical level indicator
- Rear castor wheel on request
- Hose reel on request
- Profesionalni perač pod pritiskom sa toplom vodom
- Poklopac od nerđajućeg čelika
- Robusni ram i točkovi sa punom gumom za bolju upravljivost
- Regulacija pritiska
- Termomagnetni prekidač
- Rezervoar za dizel gorivo od 20 l sa mehaničkim indikatorom nivoa
- Na zahtev zadnji okretni točak
- Na zahtev motalica creva

TECHNICAL DATA / TEHNIČKI PODACI

MODEL	AR ŠIFRA	 MAX				 MAX								 KG NET	
		bar maks.	bar radni	psi maks.	psi radni	l/h radni	gph radni	KS	kW	kW radni	o/min	V	Hz	°C maks.	kg
AR5X-10.15HM	15909	150	120	2175	1740	630	166	3	2.2	3	1450	50	230~	110	127
AR5X-15.18HT	15910	180	150	2610	2175	900	237	5,5	4	5	1450	50	400 3~	110	134

HRC+VRZ



- Triplex pump with ceramic pistons and connecting rod system with nichel plated pump head
- Flanged valve
- Automatic by-pass valve with pump head pressure discharge
- Induction motor with thermal protection
- Time delayed auto stop/start with stop for motor overloading (TST)

- Pumpa sa 3 keramička klipa, klipnjačno-kolenasti pogon, glava pumpe od niklovanog mesinga
- Prirubnički ventil
- Automatski bypass ventil sa rasterećenjem pritiska u glavi pumpe
- Indukcioni elektromotor sa termičkom zaštitom
- Potpuno zaustavljanje sa odlaganjem perača (TST)



STANDARD ACCESSORIES / SERIJSKA OPREMA



code / šifra

inlet / ulaz	M22x1,5 M	M22x1,5 M	1/4 NPT M
outlet / izlaz	M22x1,5 F	1/4 NPT F	-

compatible with / kompatibilno sa



10 m

code / šifra

inlet / ulaz	M22x1,5 F
outlet / izlaz	M22x1,5 F

LOGISTIC DATA / LOGISTIČKI PODACI

MODEL	DIM. PAKOVANJA	DIM. UREĐAJA	KG GROSS	EU	PUN KAMION	20"	40"	40"HQ
	(DxŠxV) mm	(DxŠxV) mm	kg					
AR5X-10.15HM	740x1140x1100	955x641x803	146	1	72	30	64	-
AR5X-15.18HT	740x1140x1100	955x641x803	153	1	72	30	64	-



AR6X - 15.18 HT
 AR6X - 15.23 HT
 AR6X - 21.23 HT
 AR6X - 15.23 HTF
 AR6X - 15.23 HTP



MAX bar
180÷230



MAX l/h
900÷1260



kW
5.0÷9.6



Flanged pressure unloader /
 Prirubnički regulacioni ventil



Elastic coupling /
 Elastična spojnica
 AR6X-15.23HTF



Optional hose reel /
 Opciona motačica creva

AR6X-15.23HTF

GENERAL FEATURES / OPŠTE KARAKTERISTIKE

- Professional hot water high pressure washer
- Stainless steel vertical boiler with coil burner cooling function driven by independent motor with thermal protection and double coil
- Safety pressure switch to shut down the boiler in case of lack of water
- Heating boiler shut-down delay circuit
- Pressure regulation valve
- Fuel tank with drain plug (20 l)
- Thermostat
- Water filter and fuel inlet filter
- STD for **HTP** version and optional for others models: minor leak PCB detector, flame monitoring sensor, water tank (4 l), thermal relay, contactor, descaling agent tank
- Profesionalni perač pod pritiskom sa toplom vodom
- Vertikalni kotao od inoksa, sa sistemom hlađenja gorionika pomoću ventilatora sa nezavisnim elektromotorom i dvostrukom zmijom
- Sigurnosni presostat za gašenje kotla u slučaju nedostatka vode
- Elektronika za odloženo gašenje kotla
- Regulacija pritiska
- Rezervoar za dizel gorivo 20 l, sa ispusnim čepom
- Termostat
- Filter vode i usisni filter dizel goriva
- STD** za verziju **HTP** i opciono za ostale modele: detektor curenja, senzor plamena, posuda za vodu (4 l), termički relej, kontaktor, posuda za kamenac

TECHNICAL DATA / TEHNIČKI PODACI

MODEL	AR ŠIFRA	 MAX				 MAX								 NET	
		bar maks.	bar radni	psi maks.	psi radni	l/h radni	gph radni	KS	kW	kW radni	o/min	V	Hz	°C maks.	kg
AR6X-15.18HT	15892	180	150	2610	1740	900	237	5,5	4	5	1450	50	400 3~	110	155.5
AR6X-15.23HT	15893	230	200	3335	2900	900	237	7,5	5,5	7.4	1450	50	400 3~	110	164.5
AR6X-21.23HT	15894	230	200	3335	2900	1260	333	9,6	7	9.6	1450	50	400 3~	110	164.5
AR6X-15.23HTF	15895	230	200	3335	2900	900	237	7,5	5,5	7.4	1450	50	400 3~	110	165
AR6X-15.23HTP	15996	230	200	3335	2900	900	237	8,5	6,2	7.4	1450	50	400 3~	110	164.5

HJK + VRZ



- Triplex pump with ceramic pistons and connecting rod system with nichel plated pump head
- Flanged valve
- Bronze connecting-rods
- Automatic by-pass valve with pump head pressure discharge
- Induction motor with thermal protection (Elastic coupling for HTF models)
- Time delayed auto stop/start with stop for motor overloading (TST)

- Pumpa sa 3 keramička klipa, klipnjačno-kolenasti pogon, glava pumpe od niklovanog mesinga
- Prirubnički ventil
- Bronzane klipnjače
- Automatski bypass ventil sa rasterećenjem pritiska u glavi pumpe
- Indukcioni elektromotor sa termičkom zaštitom (i elastična spojnica za mod. HTF)
- Potpuno zaustavljanje sa odlaganjem perača (TST)



STANDARD ACCESSORIES / SERIJSKA OPREMA



code / šifra

inlet / ulaz	M22x1,5 M	M22x1,5 M	1/4 NPT M
outlet / izlaz	M22x1,5 F	1/4 NPT F	-

compatible with / kompatibilno sa



10 m



code / šifra

inlet / ulaz	M22x1,5 F	-
outlet / izlaz	M22x1,5 F	-

LOGISTIC DATA / LOGISTIČKI PODACI

MODEL	DIM. PAKOVANJA	DIM. UREĐAJA	KG GROSS	EU	PUN KAMION	20"	40"	40"HQ
	(DxŠxV) mm	(DxŠxV) mm	kg	kom				
AR6X-15.18HT	740x1140x1160	980x706x900	174,5	1	72	30	64	-
AR6X-15.23HT	740x1140x1160	980x706x900	183,5	1	72	30	64	-
AR6X-21.23HT	740x1140x1160	980x706x900	183,5	1	72	30	64	-
AR6X-15.23HTF	740x1140x1160	980x706x900	184	1	72	30	64	-
AR6X-21.21HTF	740x1140x1160	980x706x900	183,5	1	72	30	64	-



AR5XE - 13.16 HT
AR5XE - 8.18 HT



MAX bar
160÷180



MAX l/h
480÷780



kW
20÷40



Flanged pressure unloader /
Prirubnički regulacioni ventil



Optional hose reel /
Opciona metalna creva

AR5X-15.23HTF

GENERAL FEATURES / OPŠTE KARAKTERISTIKE

- Professional hot water high pressure washer
- Electric boiler with continuous flow in high pressure
- Stainless steel cover
- Sturdy frame and solid rubber wheels for a better maneuverability
- Insulated heating elements
- Pressure regulation valve
- Contacting
- Water shortage four stages protection
- Safety thermostat
- Flow switch
- Easy-to-clean water filter
- Profesionalni perač pod pritiskom sa toplom vodom
- Električni protočni kotao pod visokim pritiskom
- Poklopac od nerđajućeg čelika
- Robusni ram i točkovi sa punom gumom za bolju upravljivost
- Izolovani grejni elementi
- Regulacija pritiska
- Kontaktir
- Zaštita od nedostatka vode u četiri nivoa
- Sigurnosni termostat
- Protočni prekidač
- Filter vode dostupan za pregled

TECHNICAL DATA / TEHNIČKI PODACI


MODEL	AR ŠIFRA	 MAX				 MAX											 NET
		bar maks.	bar radni	psi maks.	psi radni	l/h radni	gph radni	KS	kW	kW radni	o/min	V	A	Hz	°C maks.	kg	
AR5XE-13.16 HT	15943	160	140	2320	2030	780	206	5.5	4.1	40	1450	50	60	400 3~	110	98	
AR5XE-8.18 HT	16067	180	150	2610	2175	480	126	5.5	4.1	20	1450	50	30	400 3~	110	*	

*On request / Na zahtev

HRR + VRZ / HRC + VRZ



- Triplex pump with ceramic pistons and connecting rod system with brass pump head
- Flanged valve
- Automatic by-pass valve with pump head pressure discharge
- Induction motor with thermal protection
- Time delayed auto stop/start with stop for motor overloading (TST)
- Pumpa sa 3 keramička klipa, klipnjačno-kolenasti pogon, glava pumpe od mesinga
- Priрубnički ventil
- Automatski bypass ventil sa rasterećenjem pritiska u glavi pumpe
- Indukcioni elektromotor sa termičkom zaštitom
- Potpuno zaustavljanje sa odlaganjem perača (TST)



STANDARD ACCESSORIES / SERIJSKA OPREMA



code / šifra

inlet / ulaz	M22x1,5 M	M22x1,5 M	1/4 NPT M
outlet / izlaz	M22x1,5 F	1/4 NPT F	-

compatible with / kompatibilno sa



10 m

code / šifra

inlet / ulaz	M22x1,5 F
outlet / izlaz	M22x1,5 F

LOGISTIC DATA / LOGISTIČKI PODACI

MODEL	DIM. PAKOVANJA	DIM. UREĐAJA	KG GROSS	EU	PUN KAMION	20"	40"	40"HQ
	(DxŠxV) mm	(DxŠxV) mm	kg					
AR5XE-13.16 HT	1200x800x1137	1010x730x1007	128	1	-	-	-	-
AR5XE-8.18 HT	1200x800x1137	1010x730x1007	128	1	-	-	-	-





Stvoreno za performanse.

ECO Steam

Generalni distributer AR Professional serije za Srbiju

Vojvode Putnika 43, Trnava
35000 Jagodina, Srbija
Tel. +381 63 640 101
info@eco-steam.rs
www.eco-steam.rs
PIB 109708827 · MB 64372688

AR Professional u Srbiji

Perači pod pritiskom
Annovi Reverberi perači
Oprema i rezervni delovi
Rezervni delovi za perače

Dodatna oprema

Visokopritisne dizne
Visokopritisne spojnice i adapteri
Visokopritisna creva i motalice
Pištolji i koplja

Specijalna oprema

Filteri, dovod vode i hemije
Oprema za čišćenje cevi i kanalizacije
Oprema za peskarenje visokim pritiskom