3000

Professional Line







STEAM ITALY

ECO Steam · Vojvode Putnika 43, Trnava, 35000 Jagodina · tel. +381 63 640 101 · info@eco-steam.rs · www.eco-steam.rs

Tehnički list 3000

Steam Italy 3000 profesionalni paročistač sa usisivačem, funkcijom deterdženta i hidromlazom, kompaktan i lak za transport. Idealan za hotele, bolnice, profesionalne kuhinje i javne objekte: brza i dubinska dezinfekcija uz visoke higijenske standarde, zahvaljujući svestranom dizajnu sa trostrukom funkcijom za svakodnevnu upotrebu.
Professional steam cleaner equipped with a vacuum, detergent function and water-jet, compact and easy to carry. Ideal for hotels, hospitals, professional kitchens and public buildings: it ensures fast, deep disinfection along with high hygiene standards, thanks to its versatile triple-function design suited for daily professional use.

Tehničke karakteristike / Technical features	Podaci / Data EU	Podaci USA
Boja / Colour	Plava-siva-srebrna-zelena Blue-Grey-Silver-Green	Plava-siva-srebrna-zelena Blue-Grey-Silver-Green
Pritisak / Pressure (Bar)	8	8
Napon / Voltage	230V A/50Hz	120V AC/60Hz
Materijal kotla / Boiler material	Nerđajući čelik AISI 304 / Stainless steel AISI 304	Nerđajući čelik AISI 304 / Stainless steel AISI 304
Zapremina kotla / Boiler volume (l)	2 l	2 l
Temperatura pare u kotlu - Boiler steam temperature	171°C	171°C
Kapacitet rezervoara / Tank capacity (l)	2,2 l	2,2 l
Ukupna potrošnja snage - Total power consumption (W)	2200W	1750W
Potrošnja snage kotla - Boiler power consumption (W)	2200W	1750W
Potrošnja snage motora usisavanja - Vac motor power consumption (W)	1000W	1000W
Para EV1 / Steam EV1 (gr/min)	74 gr/min	50 gr/min
Para EV2 / Steam EV2 (gr/min)	84 gr/min	60 gr/min
Para EV1+EV2 / Steam EV1+EV2 (gr/min)	92 gr/min	65 gr/min
Količina deterdženta / Detergent quantity	10 cc/min	10 cc/min
Kapacitet deterdženta / Detergent tank capacity	1l	1 l
Alarm nivoa deterdženta / Det. level alarm	Vizuelno i zvučno / Visual and acoustic	Vizuelno i zvučno / Visual and acoustic
Snaga pumpe deterdženta / Detergent pump power	21W 220-240V AC/50Hz	17W 120V AC/60Hz
Hidromlaz + para / Steam + Hydrojet (gr/min)	312 gr/min	275 gr/min
Min. nivo otpada / Min.waste tank level	0,3l	0,3l
Kapacitet rezervoara za otpad sa prljavštinom / Waste tank level capacity used with dirt	1l	1l
Kapacitet rezervoara za otpad sa tečnošću / Waste tank level capacity used with liquid	1,8l	1,8l
Proizvodnja pare / Steam production	Kontinuirani protok sa sistemom automatskog punjenja / Continuous flow with automatic filling system	Kontinuirani protok sa sistemom automatskog punjenja / Continuous flow with automatic filling system
Snaga motora usisavanja / Vac motor power	19 Kpa	19 Kpa
Snaga pumpe vode / Water pump power	48W 220-240V AC/50Hz	51W 120V AC/60Hz
Alarm nivoa vode / Water level alarm	Vizuelno i zvučno / Visual and acoustic	Vizuelno i zvučno / Visual and acoustic
Pokazivač pritiska / Pressure indicator	Vizuelno / Visual	Vizuelno / Visual
Niski napon na ručki - Low tension voltage on handgrip	9V DC	9V DC
Vreme zagrevanja / Heating time	4 min	6 min
Kabl za napajanje / Power cable	7 mt	5 mt
Regulacija pare i usisavanja / Steam and vacuum regulation	Aktivacija na ručki pištolja - prikaz na LED panelu / Activation on the pistol grip- with indication on Led frontal pannel	Activation on the pistol grip with indication on Led frontal pannel
Dimenzije mašine (DxŠxV) / Machine dimensions	530x400x400mm	530x400x400mm
Neto težina / Net weight (Kg)	14kg	14kg
Dobijeni sertifikat / Certification reached	CE	CE

Via Muradello 1/D - Chiari (BS) - 25032 - Italia
mail: info@steamitaly.it - www.steamitaly.it
Tel.: +39 030 7080550