INOX 6000

Professional Line







STEAM ITALY

ECO Steam · Vojvode Putnika 43, Trnava, 35000 Jagodina · tel. +381 63 640 101 · info@eco-steam.rs · www.eco-steam.rs

Tehnički list Inox 6000

Steam Italy 6000 profesionalni paročistač sa usisavanjem je mašina od nerđajućeg čelika za restorane, hotele i kancelarije. Zahvaljujući dvostrukoj funkciji pare i usisavanja, uz deterdžent i hidromlaz, obezbeđuje dubinsko i higijensko čišćenje. Kontinuirana para i automatsko punjenje vodom štede vreme.

The 6000 Steam Cleaner with Vacuum is a professional stainless steel machine designed for restaurants, hotels and offices. Thanks to its dual steam and vacuum function, combined with detergent and water-jet, it ensures deep, sanitizing cleaning. Continuous steam production and automatic water refill optimize working time.

Tehničke karakteristike / Technical features	Podaci / Data EU
Boja / Colour	Čelično siva / Steel grey
Pritisak / Pressure (Bar)	10 Bar
Napon / Voltage	230V AC/50Hz
Materijal kotla / Boiler material	Nerđajući čelik AISI 304 / Stainless steel AISI 304
Zapremina kotla / Boiler volume (l)	2l
Temperatura pare u kotlu - Boiler steam temperature	184°C
Kapacitet rezervoara / Tank capacity (l)	5l
Ukupna potrošnja snage - Total power consumption (W)	3200W
Potrošnja snage kotla - Boiler power consumption (W)	3200W
Potrošnja snage motora usisavanja - Vac motor suction power (W)	1200W
Kapacitet deterdženta i tople vode / Detergent-Hot water tank capacity (l)	5l
Snaga pumpe deterdženta i tople vode / Detergent-Hot water pump power	48W 220-240V AC/50Hz
Alarm nivoa deterdženta i tople vode Detergent-Hot water tank level alarm	Vizuelno i zvučno / Visual and acoustic
Količina deterdženta - sanitacija injektiranjem / Detergent quantity-injection sanification	10 cc/min
Injektiranje tople vode + para / Hot water injection + steam	364 gr/min
Para EV1 / Steam EV1 (gr/min)	73 gr/min
Para EV2 / Steam EV2 (gr/min)	84 gr/min
Para EV1+EV2 / Steam EV1+EV2 (gr/min)	100 gr/min
Proizvodnja pare / Steam regulation	Kontinuirani protok sa sistemom automatskog punjenja / Continuous flow with automatic filling system
Min. nivo otpada - Min. waste tank level	1l
Kapacitet rezervoara za čvrst otpad / Waste tank capacity used with dirt	6,5l
Kapacitet rezervoara za tečni otpad / Waste tank capacity used with liquid	9l
Snaga motora usisavanja / Vac motor power	21,5 Kpa
Alarm nivoa vode / Water level alarm	Vizuelno i zvučno / Visual and acoustic
Pokazivač pritiska / Pressure indicator	Vizuelno / Visual
Niski napon na ručki - Low tension voltage on handgrip	9V DC
Vreme zagrevanja / Heating time	4 min
Kabl za napajanje / Power cable	7 mt
Regulacija pare / Steam regulation	Aktivacija na ručki / Activation on the pistol grip
Dimenzije mašine - Machine dimensions (DxŠxV)	440x465x705mm
Neto težina - Net weight (Kg)	37 Kg
Dimenzije ambalaže / Packaging dimensions (LxPxA)	470x590x980mm
Dobijeni sertifikat / Certification reached	CE

Via Muradello 1/D - Chiari (BS) - 25032 - Italia
mail: info@steamitaly.it - www.steamitaly.it
Tel.: +39 030 7080550