STEAM
ITALY

# INOX7000

PROFESSIONAL *Line* | 2020







**ECO Steam** · Vojvode Putnika 43, Trnava, 35000 Jagodina · tel. +381 63 640 101 · info@eco-steam.rs · www.eco-steam.rs

# INOX7000

**Profesionalni paročistač od nerđajućeg čelika (Inox). 10 bar, automatsko punjenje, usisavanje (vodeni filter), deterdžent, hidromlaz /** Professional steam cleaner in stainless steel. 10Bar pressure with automatic filling system, vacuum,detergent and hot water injection functions.

PROFESSIONAL Line | 2021

## INOX7000

| Tehničke karakteristike / Technical features | Podaci/Data |
|---|---|
| Boja / Colour | Čelično siva / Steel grey |
| Rezervoar tople vode i deterdženta / Detergent-hot water tank capacity (l) | 5 l |
| Snaga pumpe tople vode i deterdženta / Detergent-hot water pump power (l) | 48W 220-240V AC/50Hz |
| Alarm nivoa rezervoara tople vode i deterdženta / Detergent-hot water tank level alarm | Vizuelno i zvučno / Visual and acoustic |
| Količina injektiranog deterdženta / Detergent injection quantity | 10 cc/min |
| Hidromlaz + para / Hot water injection + steam gr/min | 364 gr/min |
| Pritisak / Pressure (Bar) | 10 |
| Napon / Voltage | 230 V AC / 50Hz |
| Ukupna potrošnja snage - Total power consumption (W) | 3200W |
| Potrošnja snage kotla / Boiler steam temperature (W) | 3200W |
| Potrošnja snage spoljnog usisivača / Vac motor power consumption (W) | 1200W |
| Materijal kotla / Boiler material | Nerđajući čelik AISI 304 / Stainless Steel AISI 304 |
| Zapremina kotla / Boiler volume (l) | 2 l |
| Kapacitet rezervoara / Tank capacity (l) | 5 l |
| Para EV1 / Steam EV1 gr/min | 73 gr/min |
| Para EV2 / Steam EV2 gr/min | 84 gr/min |
| Para EV1+EV2 / Steam EV1+EV2 gr/min | 100 gr/min |
| Min. nivo rezervoara za prljavštinu / Min. waste tank level | 0,3 l |
| Kapacitet rezervoara za otpad (l) sa prljavštinom / Waste tank capacity (l) used with dirt | 1 l |
| Kapacitet rezervoara za otpad (l) sa tečnošću / Waste tank capacity (l) used with liquid | 1,8 l |
| Snaga motora usisavanja / Vac motor suction power (Kpa) | 19 Kpa |
| Proizvodnja pare / Steam production | Kontinuirani protok sa sistemom automatskog punjenja / Continuous flow with automatic filling system |
| Temperatura pare u kotlu / Boiler steam temperature | 180°C |
| Snaga pumpe vode / Water pump power | 48W 220-240V AC/50Hz |
| Alarm nivoa vode / Water level alarm | Vizuelno i zvučno / Visual and acoustic |
| Pokazivač pritiska / Pressure indicator | Vizuelno / Visual |
| Niski napon na ručki / Low tension voltage on handgrip | 9V DC |
| Vreme zagrevanja / Heating time | 4 min |
| Kabl za napajanje / power cable | 7 mt |
| Regulacija pare / Steam regulation | Aktivacija na ručki pištolja - prikaz na LED panelu / Activation on the pistol grip - with indication on led frontal pannel |
| Dimenzije mašine / Machine dimensions (LxWxH) | 665x430x520mm |
| Neto težina / Net weight (Kg) | 25 Kg |
| Dimenzije ambalaže / Packaging dimensions (LxWxH) | 695x560x830mm |
| Dobijeni sertifikat / Certification reached | CE |

STEAM ITALY

Via Muradello 1/D, Chiari (BS) 25032 Italia
mail: info @steamitaly.it - www.steamitaly.it
Tel.: +39 030 7080550