INOX 7500

Professional Line





STEAM ITALY

ECO Steam · Vojvode Putnika 43, Trnava, 35000 Jagodina · tel. +381 63 640 101 · info@eco-steam.rs · www.eco-steam.rs

Tehnički list Inox 7500

Steam Italy 7500 profesionalni paročistač je izrađen od nerđajućeg čelika, sa usisavanjem, funkcijom deterdženta i hidromlazom. Idealan za industrijske pogone, auto-perionice, prehrambenu industriju, hotele, restorane i zdravstvene ustanove: dubinska higijena, brza intervencija i najviši standardi sanitacije.

Professional steam cleaner with vacuum, detergent function and hydrojet, in stainless steel.
Ideal for cleaning factories, car washes, food industry, hotels, restaurants and healthcare facilities: it ensures deep hygiene, fast intervention and the highest sanitization standards in every professional environment.

Tehničke karakteristike / Technical features	Podaci / Data EU	Podaci / Data USA
Boja / Colour	Čelično siva / Steel grey	Čelično siva
Pritisak / Pressure (Bar)	10 Bar	10 Bar
Napon / Voltage	230V AC/50Hz	110-120V AC/60HZ
Ukupna potrošnja energije / Total power consumption (W)	3200W	1750W
Potrošnja energije kotla / Boiler power consumption (W)	3200W	1750W
Potrošnja energije spoljnog usisivača / External Vac cleaner power consumption (W)	1300W	1200W
Temperatura pare u kotlu / Boiler steam temperature	184°C	184°C
Para / Steam gr/min	84 gr/min	70 gr/min
Hidromlaz + para / Hot water injection + Steam gr/min	64 gr/min	50 gr/min
Proizvodnja pare / Steam production	Kontinuirani protok sa sistemom automatskog punjenja / Continuous flow with automatic filling system	Kontinuirani protok sa sistemom automatskog punjenja
Aktivacija pare / Steam activation	Aktivacija pištoljem - prikaz na digitalnom displeju / Activation from the pistol with indication on digital display	Aktivacija pištoljem - prikaz na digitalnom displeju
Zapremina kotla / Boiler volume (l)	2 l	2 l
Materijal kotla / Boiler material	Nerđajući čelik AISI 304 / Stainless steel AISI 304	Nerđajući čelik AISI 304
Kapacitet rezervoara / Tank capacity (l)	5 l	5 l
Kapacitet kanistera deterdženta / Detergent tank capacity (l)	3 l	3 l
Kapacitet spoljnog rezervoara za otpad (l) sa prljavštinom / External waste tank capacity (l) used with dirt	15 l	15 l
Snaga pumpe deterdženta i tople vode / Detergent hot water pump power	48W 220-240V AC/50Hz	41W 120V AC/60Hz
Količina injektiranog deterdženta / Detergent injection quantity	10 cc/min	6 cc/min
Aktivacija deterdženta i tople vode / Detergent - hot water activation	Aktivacija na pištolju, izbor na panelu, prikaz na digitalnom displeju / Activation on the pistol with switch in the panel and indication in Digital display on frontal panel	Aktivacija na pištolju, izbor na panelu, prikaz na digitalnom displeju
Utičnica za spoljni usisivač / Plug for external vac cleaner	Schuko 230V	Schuko 120V
Snaga motora usisavanja / Vac motor suction power (Kpa)	23 Kpa	23 Kpa
Snaga pumpe vode / Water pump power	48W 220-240V AC/50Hz	41W 120V AC/60Hz
Alarm nivoa deterdženta i tople vode / Detergent hot water tank level alarm	Vizuelno i zvučno / Visual and acoustic	Vizuelno i zvučno
Alarm nivoa vode / Water level alarm	Vizuelno i zvučno / Visual and acoustic	Vizuelno i zvučno
Pokazivač pritiska / Pressure indicator	Vizuelno / Visual	Vizuelno
Niski napon na ručki / Low tension voltage on handgrip	9V DC	9V DC
Vreme zagrevanja / Heating time	3 min	6 min
Kabl za napajanje / Power cable	7 mt	5 mt
Dimenzije (DxŠxV) bez ručke i korpe / Machine dimensions (LxWxH) without handle and basket	665x420x520mm	665x420x520mm
Neto težina / Net weight (Kg)	40 Kg	40 Kg
Dimenzije usisivača / Vac cleaner dimensions	390x390x630mm	390x390x630mm
Težina usisivača / Vacuum cleaner weight (Kg)	10 Kg	10 Kg
Dimenzije ambalaže / Packing dimensions (LxWxH)	1050x480x660 mm	1050x480x660 mm
Dobijeni sertifikat / Certification reached	CE	CE
Količina po paleti / Pallet quantity	6	6

STEAM ITALY

Via Muradello 1/D - Chiari (BS) - 25032 - Italia
mail: info@steamitaly.it - www.steamitaly.it
Tel.: +39 030 7080550