7500XL

Professional Line







STEAM ITALY

ECO Steam · Vojvode Putnika 43, Trnava, 35000 Jagodina · tel. +381 63 640 101 · info@eco-steam.rs · www.eco-steam.rs

Tehnički list 7500XL

Steam Italy 7500XL profesionalni paročistač je vrhunska mašina od nerđajućeg čelika, namenjena velikim firmama za čišćenje, auto-perionicama i prehrambenom sektoru. Para i usisavanje sa spoljnim rezervoarom, uz hidromlaz i deterdžent za dubinsku sanitaciju. Kontinuirana proizvodnja pare, automatsko punjenje i pritisak od 10 bar štede vreme i poboljšavaju rezultate.

The 7500XL Steam Cleaner with Vacuum is a high-end professional stainless steel machine, designed for large cleaning companies, car washes and food industry sectors. Its steam and vacuum functions, with external waste tank, are combined with water-jet and detergent for deep sanitation. Continuous steam production, automatic refill and 10-bar pressure optimize both time and results.

Tehničke karakteristike / Technical features	Podaci / Data
Boja / Colour	Čelično siva / Steel grey
Kapacitet kanistera deterdženta / Detergent tank capacity (l)	3 l
Snaga pumpe deterdženta i tople vode / Detergent hot water pump power	48W 220-240V AC/50Hz
Alarm nivoa deterdženta i tople vode / Detergent hot water tank level alarm	Vizuelno i zvučno / Visual and acoustic
Količina injektiranog deterdženta / Detergent injection quantity	10 cc/min
Hidromlaz + para / Hot water injection + Steam gr/min	392 gr/min
Pritisak / Pressure (Bar)	10 Bar
Napon / Voltage	230V AC/50Hz
Ukupna potrošnja energije / Total power consumption (W)	3200-6400W
Potrošnja energije kotla / Boiler power consumption (W)	3200-6400W
Potrošnja energije spoljnog usisivača / External Vac cleaner power consumption (W)	1300W
Utičnica za spoljni usisivač / Plug for external vac cleaner	Schuko 230V
Materijal kotla / Boiler material	Nerđajući čelik AISI 304 / Stainless steel AISI 304
Zapremina kotla / Boiler volume (l)	2 l
Kapacitet rezervoara / Tank capacity (l)	5 l
Para / Steam gr/min	156 gr/min
Kapacitet spoljnog rezervoara za otpad (l) sa prljavštinom / External waste tank capacity (l) used with dirt	22 l
Snaga motora usisavanja / Vac motor suction power (Kpa)	23 Kpa
Proizvodnja pare / Steam production	Kontinuirani protok sa sistemom automatskog punjenja / Continuous flow with automatic filling system
Temperatura pare u kotlu / Boiler steam temperature	184°C
Snaga pumpe vode / Water pump power	48W 220-240V AC/50Hz
Alarm nivoa vode / Water level alarm	Vizuelno i zvučno / Visual and acoustic
Pokazivač pritiska / Pressure indicator	Vizuelno / Visual
Niski napon na ručki / Low tension voltage on handgrip	9V DC
Vreme zagrevanja / Heating time	3 min
Kabl za napajanje / Power cable	7 mt
Aktivacija pare / Steam activation	Aktivacija na ručki pištolja - prikaz na digitalnom displeju / Activation on the pistol grip - with indication on led frontal pannel
Aktivacija deterdženta i tople vode / Detergent - hot water activation	Aktivacija na ručki pištolja sa izborom na panelu i prikazom na digitalnom displeju / Activation on the pistol grip with selection switch in the front pannel and indication in Digital display on frontal pannel
Dimenzije (DxŠxV) bez ručke i korpe / Machine dimensions (LxWxH) without handle and basket	665x420x520 mm
Neto težina / Net weight (Kg)	40 Kg
Dimenzije usisivača / Vac cleaner dimensions	390x390x630 mm
Težina usisivača / Vacuum cleaner weight (Kg)	10 Kg
Dimenzije ambalaže (LxWxH)	1050x480x660 mm
Dobijeni sertifikat	CE

Via Muradello 1/D - Chiari (BS) - 25032 - Italia
mail: info@steamitaly.it - www.steamitaly.it
Tel.: +39 030 7080550