INOX 8000

Professional Line







STEAM ITALY

ECO Steam · Vojvode Putnika 43, Trnava, 35000 Jagodina · tel. +381 63 640 101 · info@eco-steam.rs · www.eco-steam.rs

Tehnički list Inox 8000

Steam Italy 8000 profesionalni paročistač je mašina od nerđajućeg čelika za hotele, bolnice, profesionalne kuhinje i javne objekte. Zahvaljujući kontinuiranoj proizvodnji pare, automatskom punjenju vodom i temperaturi do 184°C, obezbeđuje brzu i efikasnu higijenizaciju.
The Professional Steam Cleaner 8000 is a stainless steel machine designed for hotels, hospitals, professional kitchens and public buildings. Thanks to continuous steam production, automatic water refill and temperatures up to 184°C, it delivers fast, effective sanitation.

Tehničke karakteristike / Technical features	Podaci / Data EU	Podaci / Data USA
Boja / Colour	Čelično siva / Steel grey	Čelično siva
Kapacitet kanistera deterdženta / Detergent tank capacity (l)	3 l	3 l
Kapacitet kanistera tople vode / Hot water tank capacity (l)	5 l	5 l
Snaga pumpe deterdženta i tople vode / Detergent-hot water pump power	48W 220-240V AC/50Hz	17W 120V AC/60Hz
Alarm nivoa deterdženta i tople vode / Detergent-hot water tank level alarm	Vizuelno i zvučno / Visual and acoustic	Vizuelno i zvučno
Količina injektiranog deterdženta / Detergent injection quantity	10 cc/min	10 cc/min
Hidromlaz + para / Hot water + steam gr/min	364 gr/min	245 gr/min
Pritisak / Pressure (Bar)	10 Bar	10 Bar
Napon / Voltage	230V AC/50Hz	120V AC/60Hz
Ukupna potrošnja snage / Total power consumption (W)	3200W	1750W
Potrošnja snage kotla / Total boiler consumption (W)	3200W	1750W
Materijal kotla / Boiler material	Nerđajući čelik AISI 304 / Stainless steel AISI 304	Nerđajući čelik AISI 304
Zapremina kotla / Boiler volume (l)	2 l	3,4 l
Kapacitet rezervoara / Tank capacity (l)	5 l	5 l
Para EV1 / Steam EV1 gr/min	73 gr/min	55 gr/min
Para EV2 / Steam EV2 gr/min	84 gr/min	66 gr/min
Para EV1+EV2 / Steam EV1+EV2 gr/min	100 gr/min	76 gr/min
Kapacitet spoljnog rezervoara za čvrst otpad / Solid waste collection tank capacity (W)	15 l	15 l
Snaga motora usisavanja - Vac motor suction power (Kpa)	23 Kpa	23 Kpa
Proizvodnja pare / Steam production	Kontinuirani protok sa sistemom automatskog punjenja / Continuous flow with automatic filling system	Kontinuirani protok sa sistemom automatskog punjenja
Temperatura pare u kotlu - Boiler steam temperature (C°)	184 °C	184 °C
Snaga pumpe vode / Water pump power	48W 220-240V AC/50Hz	51W 120V AC/60Hz
Alarm nivoa vode / Water level alarm	Vizuelno i zvučno / Visual and acoustic	Vizuelno i zvučno
Pokazivač pritiska / Pressure indicator	Vizuelno / Visual	Vizuelno
Niski napon na ručki - Low tension voltage on handgrip	9V DC	9V DC
Vreme zagrevanja / Heating time	4 min	8 min
Kabl za napajanje / Power cable	7 mt	5 mt
Aktivacija pare / Steam activation	Aktivacija na ručki - prikaz na LED panelu / Activation on the pistol grip with indication on led frontal pannel	Aktivacija na ručki pištolja - prikaz na LED panelu
Aktivacija deterdž.-hidromlaza - Detergent-hot water activation	Aktivacija na ručki, birač na panelu, prikaz na digitalnom displeju / Activation on the pistol grip and indications on led frontal pannel digital display	Aktivacija na ručki, prikaz na LED panelu i digitalnom displeju
Dimenzije mašine - Machine dimensions (DxH)	320x400x320mm	320x400x320mm
Neto težina / Net weight (Kg)	17 Kg	17 Kg
Dimenzije ambalaže - Packaging dimensions (LxWxH)	470x400x320mm	470x400x320mm
Dobijeni sertifikat / Certification reached	CE	CE

Via Muradello 1/D - Chiari (BS) - 25032 - Italia
mail: info@steamitaly.it - www.steamitaly.it
Tel.: +39 030 7080550