XSTEAM 18K

Industrial Line





STEAM ITALY

ECO Steam · Vojvode Putnika 43, Trnava, 35000 Jagodina · tel. +381 63 640 101 · info@eco-steam.rs · www.eco-steam.rs

Tehnički list XSteam 18k

Steam Italy XSTEAM 18K industrijski paročistač je naše rešenje za profesionalno čišćenje parom. Kombinuje četiri funkcije u jednoj: para, deterdžent, hidromlaz i usisavanje, uz maksimalnu svestranost i visoke performanse. Ključna novina je istovremeni rad dva operatera zahvaljujući dvostrukom priključku (samo para ili para i usisavanje), čime se skraćuje vreme rada i uvek obezbeđuje dubinsko i efikasno čišćenje.
XSTEAM 18K is our industrial solution for professional steam cleaning. It combines four functions in one: steam, detergent, hydro-jet, and suction, delivering maximum versatility and high performance. A key innovation is the ability for two operators to work simultaneously using dual connections (steam only or steam & suction), reducing cleaning time while ensuring a deep and effective clean.

Tehničke karakteristike	Podaci EU
Boja / Colour	Čelično siva / Steel grey
Kapacitet deterdženta / Detergent tank capacity (l)	5 l
Kapacitet rezervoara tople vode (isti kao rezervoar vode) / Hot water tank capacity (same tank of water)	11 l
Snaga pumpe deterdženta, tople vode i antikamenca / Detergent-hot water-antilimestone pump power	150W 220-240V AC/50Hz
Alarm nivoa deterdženta i vode / Detergent-hot water level alarm	Vizuelno i zvučno / Visual and acoustic
Injektiranje deterdženta + para / Detergent injection + Steam gr/min	590 gr/min
Injektiranje tople vode + para / Hot water injection + Steam gr/min	780 gr/min
Pritisak / Pressure (Bar)	10
Napon / Voltage	380V AC/50Hz
Ukupna potrošnja energije / Total power consumption (W)	19300W
Potrošnja energije kotla / Boiler steam temperature (W)	18000W
Potrošnja energije spoljnog usisivača / External vac cleaner consumption (W)	1300W
Utičnica usisivača / Socket for external vacuum cleaner	Schuko 230V 16A
Materijal kotla / Boiler material	Nerđajući čelik AISI 304 / Stainless steel AISI 304
Zapremina kotla / Boiler volume (l)	7 l
Izlaz pare 1 / Steam socket 1 gr/min	0 - 550 gr/min
Izlaz pare 2 / Steam socket 2 gr/min	0 - 220 gr/min
Kapacitet rezervoara za čvrst otpad / Waste tank capacity (l) used with dirt	20 l
Snaga motora usisavanja / Vac motor suction power (Kpa)	21,6 Kpa
Proizvodnja pare / Steam production	Kontinuirani protok sa sistemom automatskog punjenja / Continuous flow with automatic filling system
Temperatura pare u kotlu / Boiler steam temeprature	184°C
Alarm nivoa vode / Water level alarm	Vizuelno i zvučno / Visual and acoustic
Pokazivač pritiska / Pressure indicator	Vizuelno / Visual
Niski napon na ručki / Low tension voltage on handgrip	9V DC
Vreme zagrevanja / Heating time	4 min
Kabl za napajanje / Power cable	7 mt sa utikačem 380V 32A / 7 mt with 380V 32A plug (3L+N+GND)
Aktivacija pare / Steam activation	Aktivacija na prednjem panelu - prikaz na digitalnom displeju / Activation on the front pannel - with indication in digital display
Aktivacija usisavanja / Vacuum activation	Aktivacija na prednjem panelu - prikaz na digitalnom displeju / Activation on the front pannel - with indication in digital display
Aktivacija tople vode i deterdženta / Detergent-hot water activation	Aktivacija na prednjem panelu - prikaz na digitalnom displeju / Activation on the front pannel - with indication in digital display
Dimenzije (DxŠxV) bez drške i korpe / Machine dimensions (LxWxH) no handle and baskets	960x623x750mm
Neto težina / Net weight (Kg)	80 Kg
Dimenzije usisivača / Vacuum cleaner dimensions	450x450x30mm
Dimenzije ambalaže (LxWxH) / Packaging dimensions (LxWxH)	1175x1000x840mm
Dobijeni sertifikat / Certification reached	CE

Via Muradello 1/D - Chiari (BS) - 25032 - Italia
mail: info@steamitaly.it - www.steamitaly.it
Tel.: +39 030 7080550